

Client IPv6 Addressing

ISP Workshops



These materials are licensed under the Creative Commons Attribution-NonCommercial 4.0 International license (<http://creativecommons.org/licenses/by-nc/4.0/>)

Last updated 15th January 2019

Acknowledgements

- This material originated from the Cisco ISP/IXP Workshop Programme developed by Philip Smith & Barry Greene
- Use of these materials is encouraged as long as the source is fully acknowledged and this notice remains in place
- Bug fixes and improvements are welcomed
 - Please email *workshop (at) bgp4all.com*

Philip Smith

Client IPv6 Addressing



IPv6 Addressing on LANs (fixed & wireless)

- StateLess Address AutoConfiguration (SLAAC)
 - Client learns IPv6 address, default gateway, and DNS resolver, from the router on the LAN

- DHCPv6
 - Client learns IPv6 address, default gateway, and DNS resolver, from a DHCP server
 - Can be on the same LAN (not advised)
 - Can be the router (usually limited feature set)
 - Standalone, via DHCP relay on the router (most common)

SLAAC: Router side

- Router does not need any specific configuration
 - But there are some good practice suggestions to improve general behaviour
 - Setting router preference high (default is medium)
 - Make the RA interval 30 seconds
 - If supported, also supply DNS resolver using RA
 - Set Multicast Listener Discovery query interval to 30 seconds

```
interface FastEthernet0/0
  ipv6 address 2001:DB8:100::1/64
  ipv6 nd router-preference high
  ipv6 nd ra interval 30
  ipv6 nd ra dns server 2001:DB8:100:F::53
  ipv6 mld query-interval 30
!
```

SLAAC: Client side

- IPv6 client learns address “from the LAN”
 - IPv6 is enabled on most end-user devices today
 - Laptop, PC, tablet, smartphone
 - Device sends out “router solicit”
 - Router responds with “router advertisement” containing subnet and default gateway
 - Initial client state (eg macOS laptop):

```
Client:
en3: flags=8863<UP,BROADCAST,SMART,RUNNING,SIMPLEX,MULTICAST> mtu 1500
    ether 68:5b:35:7d:3b:bd
    inet6 fe80::6a5b:35ff:fe7d:3bbd%en3 prefixlen 64 scopeid 0x8
```

SLAAC

□ On receiving response from the router:

```
en3: flags=8863<UP,BROADCAST,SMART,RUNNING,SIMPLEX,MULTICAST> mtu 1500
    ether 68:5b:35:7d:3b:bd
    inet6 fe80::6a5b:35ff:fe7d:3bbd%en3 prefixlen 64 scopeid 0x8
    inet6 2001:db8:100::6a5b:35ff:fe7d:3bbd prefixlen 64 autoconf
    inet6 2001:db8:100::18eb:2861:458e:862b prefixlen 64 autoconf temporary
    nd6 options=1<PERFORMNUD>
```

Internet6:

Destination	Gateway	Flags	Netif	Expire
default	fe80::219:30ff:fee	UGc	en3	

- Note the temporary address – this is the one used for all IPv6 connectivity, and has a lifetime determined by the client's operating system

Stateful DHCPv6

- Behaves like DHCP on IPv4 infrastructure:
 - DHCPv6 server distributes host address from a pool on request from client
 - DHCPv6 client configures IPv6 address, default gateway, and DNS resolver
 - Sample server configuration (Cisco IOS)

```
ipv6 dhcp pool LABNET
  dns-server 2001:DB8:100:F::53
  domain-name labnet
!
interface VLAN1
  ipv6 address 2001:DB8::1/64
  ipv6 nd managed-config-flag
  ipv6 nd other-config-flag
  ipv6 dhcp server LABNET
!
```

IPv6 address distributed by DHCPv6

DNS & other settings distributed by DHCPv6

Stateless DHCPv6

- Where DHCPv6 is used to distribute other information
 - But not IPv6 addresses (usually done by SLAAC)
 - Documented in RFC3736
- For example:
 - SLAAC is used to distribute IPv6 address and default gateway
 - DHCPv6 is used to provide DNS resolver and other network information
 - Compare this configuration with that from the earlier example

DNS & other settings distributed by DHCPv6

```
ipv6 dhcp pool LABNET
  dns-server 2001:DB8:100:F::53
  domain-name labnet
!
interface VLAN1
  ipv6 address 2001:DB8::1/64
  ipv6 nd other-config-flag
  ipv6 dhcp server LABNET
!
```

Distributing subnets to End-Users

- Static assignment (as in IPv4)
 - Tell the customer what subnet they have
 - Not dynamic!
 - Usually with Internet service documentation

- DHCPv6-PD
 - Use DHCPv6 Prefix Delegation feature to distribute subnets automatically
 - Prefix delegated can optionally be made persistent if desired

DHCPv6-PD

- New for IPv6, is Prefix-Delegation (PD)
 - Allows DHCP server to delegate subnets to clients
 - Especially useful for Broadband deployments
 - Also can be used for enterprise
 - Server example on BRAS (Cisco IOS)
 - Distribute /56 to client network out of /40 pool

```
ipv6 dhcp pool BB-CUST-1
  prefix-delegation pool BBCUST1 lifetime 1800 600
!
ipv6 local pool BBCUST1 2001:DB8:F00::/40 56
!
interface FastEthernet0/0
  ipv6 enable
  ipv6 dhcp server BB-CUST-1
!
```

DHCPv6-PD

- Client receives IPv6 subnet from the server
- Client then automatically assigns a /64 to each active interface on the router
- This means that the network operator can prepare a standard configuration for each client
 - No IPv6 address dependencies
 - Flexibility to change delegated prefix as required
- Many client side routers (CPE) support DHCPv6-PD

DHCPv6-PD – Cisco IOS example

- Cisco IOS uses a “general prefix” concept
 - The received subnet is stored in a user defined “variable”
 - This variable is then used on internal interfaces to give each a /64 subnet
 - For example:
 - Prefix received is 2001:DB8:C:80::/56 -> General Prefix
 - Final 72 bits are set by the user, taking the form ::<subnet>:0:0:0:1
 - Interfaces will be addressed 2001:DB8:C:80::1/64, 2001:DB8:C:81::1/64, 2001:DB8:C:82::1/64 etc, in sequence
- Receiving interface also configured automatically as the default gateway

DHCPv6-PD – Client Configuration

□ Cisco IOS client configuration example:

```
interface Dialer0
  description ADSL link to MY ISP
  ipv6 address autoconfig default
  ipv6 dhcp client pd ADSL-PD rapid-commit
!
interface Vlan1
  description Home Network
  ipv6 address ADSL-PD ::0:0:0:0:1/64
!
interface Vlan2
  description Home IP/TV Network
  ipv6 address ADSL-PD ::1:0:0:0:1/64
!
interface Vlan3
  description Home Wireless Network
  ipv6 address ADSL-PD ::2:0:0:0:1/64
!
```

Signifies default interface, for default route

Speeds up DHCP configuration between client and server, using 2 messages rather than 4

DHCPv6-PD – Client Configuration

- Cisco IOS client interface status example:

```
router# sh ipv6 interface brief
Vlan1      [up/up]
    FE80::C800:E7FF:FE22:8
    2001:DB8:F00:3100::1
Vlan2      [up/up]
    FE80::C800:E7FF:FE22:6
    2001:DB8:F00:3101::1
Vlan3      [up/up]
    FE80::C800:E7FF:FE22:4
    2001:DB8:F00:3102::1
...etc...
```

DHCPv6-PD Servers ?

- Many vendor hardware products
 - Routers, firewalls, etc
- Example of standalone software (like IPv4 DHCP):
 - ISC's DHCP server
 - ISC's KEA (replaces ISC's DHCP server)
 - <http://kea.isc.org>
 - Jagornet DHCP server
 - <http://www.jagornet.com>
- Persistent address delegation
 - Available using DHCP Option 37 "remote hardware ID"
 - The client gets the same address block delegated each time

Client IPv6 Addressing



ISP Workshops